




Adjustable Height Aluminum Tripod

Wallace Cranes offers portable aluminum adjustable tripods in 1-5 ton capacities. These lightweight models are easily transportable and can be assembled/disassembled quickly making them an ideal choice for repair and maintenance jobs located off-site. In addition, our tripods are recommended to help set-up our larger cranes when a forklift or overhead lifting equipment is not available. All units include a standard base with lashing cable to prevent overspreading of legs. Rubber Base Pad Kits, Mud Base Plate Kits, and Spike Base Kits are optional accessories available for every model.

Product Features

- Aluminum Construction
 - Sturdy lightweight construction for quick set-up and take-down
 - Easily transportable
- Available in 1 to 5 Ton Capacities
- Adjustable heights available from 5'6" - 19'0"
- Machined alloy heads holds free swiveling eye-bolt which always hangs plumb
- Spring loaded bolt (adjustable models only) locks in "out" position
- Legs rest securely on standard base - optional base accessories available for different surfaces
- Lashing kit provides an extra precaution against slipping and can be used with all base accessories



Click to enlarge

Heights under eyebolt are figured for optimum strength
(C) not exceeding 75% of adjusted (B).

Crane Sizes and Model Numbers

Rated Capacity	Model Number	A		B		C		Net Wt.	Spike Base Model Number
		Height - Eye Bolt to Floor		Overall Length		Distance Between Legs			
		Max.	Min.	Max.	Min.	Max.	Min.		
1 Ton	R3-282	10'10"	7'1"	12'9"	8'9"	111"	63"	79	676
	H3-2142	19'0"	12'9"	21'9"	14'9"	192"	108"	216	1514
2 Ton	H3-4122	16'4"	11'0"	18'9"	12'9"	165"	93"	174	1514
3 Ton	R3-642	5'6"	3'8"	6'9"	4'9"	57"	33"	57	676
	R3-662	8'2"	5'6"	9'9"	6'9"	84"	48"	70	676
4 Ton	H3-8102	12'11"	8'5"	15'9"	10'9"	138"	78"	156	1514
5 Ton	H3-1062	7'6"	4'11"	9'9"	6'9"	84"	48"	111	1514
	H3-1082	10'3"	6'8"	12'9"	8'9"	111"	63"	124	1514

Note: Rated capacity is in thousands of pounds. Capacities derated at no additional charge. Simply change number in red to require capacity accordingly when ordering.